

## Series 375 Aluminum Single Hung Tilt-Sash Window

Also Available: Insulated Slider, Insulated Picture Window and Insulated Shapes

- Aluminum frame and sash components are precision cut and assembled to make joints weather-tight
- Warm-edge insulated glass reduces condensation and improves thermal efficiency
- Sashes interlock for added strength and security
- Weather stripping at interlock and sash stile helps block air and water infiltration
- Positive sash lock provides security and helps keep the frame and sash weather-tight
- Tilt latch releases bottom sash for tilt-in function
- Full perimeter weather-strip insulation provides energy saving thermal efficiency

- 9/16" insulating glass boosts thermal performance
- Vinyl bulb seal spans bottom of operable sash to minimize air and water infiltration
- Continuous extruded nail-fin on all frame sections for fast, easy installation
- 1" nail-fin setback for brick veneer construction and selected stucco applications
- Sloped-sill allows for easy water run-off
- DP Rating R40 (window size tested 48" x 84")
- Jamb depth: 2.5625"





## Color Options\*\*



## **Custom Options**

- Low-E Glass
- Low-E Glass / Argon Gas
- Ultra Low-E / Argon Gas (may be required for Energy Star rating)
- 5/8" or 3/4" flat grids available
- Custom sizes available
- DP-50 (window size tested 48" x 72")

Scan and Experience the WeatherLok Website



<sup>\*</sup>Screens are not meant to restrain a child from falling through an open window

<sup>\*\*</sup>Printing process may affect color shown. Please refer to actual window sample when selecting colors.

Manufacturer reserves the right to substitute components as necessary for continued product improvement. WL-375-1/15